



ARCHITECTURAL SPECIFICATIONS CLASSIC CORK GLUE DOWN TILES

Style:	Cork Tiles for floors and walls
Description:	Homogenous or veneer cork
Thickness :	1/8" standard - 5/16" custom available
Density:	500kg/m3 on average
Nominal Sizes:	12" x 12" or 12" x 24" - custom sizes available
Finish:	Water-based polyurethane finish **Custom sizes and colors available

PERFORMANCE CHARACTERISTICS

Compression and Recovery (ISO 9727) : 1.5% residual after one hour with loading of 7 kg/ cm²

Slip Resistance (ASTM C1028): Dry: 0.70 Wet : 0.73

Fire Rating (E-684) : Class II

Accoustical Performance: FSTC 53 - FIIC 67 60
Test conducted over 8" concrete slab

GREEN FEATURES

Our Cork Glue Down Tiles may contribute to LEED® points in the following categories :

MR:	4.1/ 4.2	Recycled Content (pre-consumer)
IAC:	4.2 / 4.3	Low-emission adhesive and product
MR:	5.1/5.2	Manufactured within 500 miles of project *
Renewable:	6.0	Rapidly renewable resource and material

Our cork uses a formaldehyde-free polyurethane- non-toxic polymer suitable for food contact as a binder for the cork granules.

* Contact us for details as to radius and geographic qualifications for your specific project.