



ARCHITECTURAL SPECIFICATIONS

THE ECHELON COLLECTION RECYCLED LEATHER TILES

LEATHER SPECIFICATIONS

Style:	Recycled Leather Tiles (RLT)
Description:	Full-grain leather shredded bound with natural rubber and composites
Thickness:	1/8" or 1/16" (3.0 mm or 1.5 mm)
Weight:	9.5 per square feet (1/8") 4.8 oz. per square feet (1/16")
Sizes:	4" x 4" up to 24" x 24"
Maximum Size:	54" width x 100' length
Finish:	Specialty finish designed for leather

PERFORMANCE CHARACTERISTICS

Wear Resistance – Fricke-Taber Test (EN 660-2):	2.06 mg/100 revolutions
Abrasion Test ASTM D4060 (CS-17, 1 kg):	102 mg/1,000 cycles
Slip Resistance (SATRA TM 144):	Wet: 0.27 Dry: 0.76
Single-Flame Source Test (ISO 11925):	Pass
Breaking Force (ASTM D-2208)	600+ lbs
Elongation (ASTM D-2211 (psi)	0-50%
Static Load Limit (ASTM F-970) (100 lbs psi)	.0004 inch

GREEN FEATURES

VOC Emission (ISO 14814 – Water Method)	Class None as Detected (less than 20 mg/kg)
Natural and Rapidly Renewable Products	Leather, Latex, Acacia Tree Bark

EcoDomo LLC is a member of the US Green Building Council and CoopAmerica. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.EcoDomo.com for more details.