



ARCHITECTURAL SPECIFICATIONS

BEAUTICORK COLLECTIONS FLOATING CORK PLANKS AND TILES

SPECIFICATIONS

STYLE: FLOATING CORK TILES A/O PLANKS WITH CORK BACKING.
AVAILABLE WITH BEVELED EDGES (EDGEMAX) OR STANDARD (CLASSIC).

DESCRIPTION: HOMOGENOUS OR VENEER CORK MOUNTED ON A FORMALDEHYDE-FREE HIGH-DENSITY FIBERBOARD BACKED WITH CORK WITH UNICLIC® INTERLOCKING JOINT SYSTEM

THICKNESS : 3/8"

WEIGHT: 14 OZ. PER SQUARE FEET

NOMINAL SIZES: 15" x 15" x 3/8" - 7.5" x 36" x 3/8" - EDGEMAX BEVELED CORK
7.5" x 36" x 3/8" - 12" x 36" x 3/8" - CLASSIC CORK

FINISH: WATER-BASED WARRANTIED FLOOR FINISH (5 COMMERCIAL/25 YEARS RESIDENTIAL)

CUSTOM SIZES AND COLORS AVAILABLE

PERFORMANCE CHARACTERISTICS

TABER TEST (ASTM D 4060 – CS 17 WHEEL, 500 GR): 11,500 WEAR THROUGH CYCLES

STATIC LOAD LIMIT (ASTM F970) : 004 INCH

SLIP RESISTANCE (ASTM C 1028) : DRY: 0.95 WET : 0.96

COLORFASTNESS (AATC- 100 HRS) : CLASS 1

RADIANT FLUX (C –ASTM E 648) : 0.25 (CLASS II)

FLAME SPREAD (ASTM E-84) : CLASS B

FIIC TEST (ASTM E989)* : 60 (NO UNDERLAY) 59 (WITH UNDERLAY)
TEST CONDUCTED OVER 8" CONCRETE WITH NO SUSPENDED CEILING

Low-VOC (C-01350) : PASS
CALIFORNIA STANDARD PUBLIC SCHOOL 01350

GREEN FEATURES

OUR CORK FLOATING TILES MAY CONTRIBUTE TO LEED FOR COMMERCIAL INTERIORS IN :

MR - 4.1 / 4.2 RECYCLED CONTENT (PRE-CONSUMER)

IAC - 4.2 / 4.3 LOW-EMISSION ADHESIVE AND PRODUCT

RENEWABLE- 6.0 RAPIDLY RENEWABLE RESOURCE AND MATERIAL

EcoDomo LLC IS A MEMBER OF THE US GREEN BUILDING COUNCIL AND COOPAMERICA. WE CONSIDER PAYING FOR CARBON CREDITS, WIND-GENERATED ELECTRICITY, AND RECYCLED MATERIALS AS ESSENTIAL AS PAYING FOR RENT AND OTHER UTILITIES. VISIT WWW.ECODOMO.COM FOR MORE DETAILS.