



ARCHITECTURAL SPECIFICATIONS

RAINFOREST COLLECTION FLOATING RECYCLED LEATHER PLANKS AND TILES

SPECIFICATIONS

| | |
|-----------------------|--|
| Style: | Floating Recycled Leather tiles a/o planks with cork backing |
| Description: | Recycled leather mounted on a formaldehyde-free high-density fiberboard backed with cork with Unielic® interlocking joint system |
| Thickness : | 3/8" |
| Weight: | 16 oz. per square foot |
| Nominal Sizes: | 15" x 15" x 3/8" and 7.5" x 36" x 3/8" |
| Finish: | Water-based warranted floor protective finish (5 years commercial/ 25 residential) |

**Custom sizes and colors available

PERFORMANCE CHARACTERISTICS

| | | |
|---|---------------------------|--------------------|
| Taber Test (ASTM d 4060 – CS 17 wheel, 500 gr): | 8,000 wear through cycles | |
| Static Load Limit (ASTM F970) : | 005 inch | |
| Slip Resistance (ASTM C1028) : | Dry: 0.98 | Wet : 0.98 |
| Colorfastness (AATC- 100 hrs) : | Class IV | |
| Critical Radiant Flux (C –ASTM e 648) : | 0.41 (Class II) | |
| Surface Burning Characteristics (ASTM E-84) : | Class C | |
| FIIC Test (ASTM E989): Test conducted over 8" concrete with <u>no</u> suspended ceiling | 59 (no underlay) | 61 (with underlay) |
| Low-VOC (California standard Public School 01350) : | Pass | |

GREEN FEATURES

Our recycled leather Floating Tiles may contribute to LEED for Commercial Interiors in :

| | | |
|-------------------|-----------|---|
| MR: | 4.1/ 4.2 | Recycled Content (pre-consumer) |
| IAC: | 4.2 / 4.3 | low-emission adhesive and product |
| Renewable: | 6.0 | Rapidly renewable resource and material |

EcoDomo LLC is a member of the US Green Building Council and CoopAmerica. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.EcoDomo.com for more details.