
ECHELON ARCHITECTURAL SPECIFICATIONS

ECHELON GLUE DOWN TILES

Style:	Recycled Leather Tiles (RLT)
Description:	Full-grain leather shredded bound with natural rubber and composites
Thickness:	1/8" or 3mm
Weight:	9.5 per square feet (1/8")
Available Sizes:	9" x 18" – 12" x 12" – 18" x 18" ** Custom sizes available**
Maximum Size:	24" x 24"
Finish:	Specialty finish designed for leather floors or wall tiles

PERFORMANCE CHARACTERISTICS

Wear Resistance – Frick-Taber Test (EN 660-2):	2.06 mg/100 revolutions
Abrasion Test ASTM D4060 (CS-17, 1 kg):	102 mg/1,000 cycles
Slip Resistance (SATRA TM 144):	Wet: 0.27 Dry: 0.76
Single-Flame Source Test (ISO 11925):	Pass
Flame Spread Test (ASTM E-84):	Class "C" standard Class "B" available as an upgrade
Breaking Force (ASTM D-2208):	600+ lbs
Elongation (ASTM D-2211) (psi):	0-50%
Static Load Limit (ASTM F-970) (100 lbs psi):	0.0004 inch



Leather Surfacing and Fabrication Company

GREEN FEATURES

VOC Emission (ISO 14814 – Water Method)

Class None as Detected (less than 20 mg/kg)

Natural and Rapidly Renewable Products

Leather, Latex, Acacia Tree Bark

- **MR:** 4.1/ 4.2 Recycled Content (pre-consumer)
- **IAC:** 4.2 / 4.3 Low-emission adhesive and product
- **Renewable:** 6.0 Rapidly renewable resource and material

EcoDomo LLC is a member of the US Green Building Council and can contribute to LEED Certification. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.ecoDomo.com for more details.

Manufactured in the United States of America

2022 All rights reserved.